


RADA VR2 VANDAL RESISTANT SHOWER HEADS



- WRAS Approved
- Vandal resistant showerheads
- Available for exposed or concealed applications
- Combines style with high performance
- Ideal for leisure facilities, secure establishments, schools and student accommodation
- Polished chrome plated to a high standard
- Easy to fit and secure installation
- Choice of 9 l/min or 6 l/min flow regulator (supplied) for water economy



Dimensions (mm)

**Specify as: Rada VR2-RS (2.1652.009)**

For connection to concealed pipework. 1/2" BSP connection. With fixed spray plate and 9 l/min flow regulator (6.0 l/min regulator supplied).


Specify as: Rada VR2-ES (2.1652.011)

For connection to rising surface pipework. 15 mm push-fit pipe connection. With fixed spray plate and 9 l/min flow regulator (6.0 l/min regulator supplied).

Specify as: Rada VR2-CC (2.1652.010)

For connection to concealed pipework. 15 mm compression fitting connection. With fixed spray plate and 9 l/min flow regulator (6.0 l/min regulator supplied).

Flow Diagram



TECHNICAL SPECIFICATION

Installation and Maintenance

Please refer to the appropriate Product Manual.

Connections

- VR2-RS - 1/2" BSP connection
- VR2-ES - 15 mm push-fit pipe connection
- VR2-CC - 15 mm compression

Approvals

WRAS Approved (Water Regulations Advisory Scheme)
 Designed, manufactured and supported in accordance with accredited
 BS EN ISO 9001:2008 Quality Management Systems and
 BS EN ISO 14001:2004 Environmental Management Systems.

Materials

Shower head: Brass, polished chrome finish.
 Spray Cartridge: Engineering plastic.
All screws in contact with water are stainless steel.

Temperature Range

Designed to accept water supplied between 5°C and 90°C.

Pressure Range

Shower head: Recommended minimum maintained pressure at the inlet of the fitting: 0.2 bar. Maximum maintained pressure at the inlet of the fitting: 5.0 bar (with flow regulator fitted).

Spray Performance

Minimum flow rate necessary to achieve a fully formed spray pattern:
 4.5 litres/min.



Accessories

VR Security Kit (5.936.94.1.0) - Concealed mounting kit offering even greater security. For use with VR2-RS and VR2-CC.

AD35 Extended Connection Nipple (1.555.74.2.0) - 250 mm x 1/2" BSP parallel nipple.

Rada Riser Pipe (5.936.03.1.0) - 700 mm stainless steel supply pipe. For use with VR2-ES.

Spray Patterns at 9 l/min



Kohler Mira Limited
 Cromwell Road, Cheltenham
 Gloucestershire, GL52 5EP

Specification Enquiries
 Tel: 0844 571 1777, Fax: 0844 472 3076
 Email: rada_technical@mirashowers.com
 www.radacontrols.com

Rada is a registered trademark of Kohler Mira Limited.
 The company reserves the right to alter product specification without notice.
 © January 2012 Kohler Mira Limited. All rights reserved.
 No part of this document, or any accompanying document, may be reproduced or transmitted in any form or by any means, including photocopying or electronically, without the permission of Kohler Mira Limited.

A **KOHLER** COMPANY

